

80.0A 200V Schottky Barrier Rectifiers
Features

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Construction utilizes void-free molded plastic technique
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed
260°C/10 seconds at terminals


Mechanical Data

Case : Molded plastic body

Terminals : Solder plated, solderable per MIL-STD-750, Method 2026

Polarity : Polarity symbol marking on body

Mounting Position : Any






Maximum Ratings (Ta=25°C unless otherwise specified)

PARAMETER	SYMBOLS	ASBMBR80200PTRX0	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	200	V
Maximum RMS voltage	V_{RMS}	140	V
Maximum DC blocking voltage	V_{DC}	200	V
Maximum average forward rectified current at Tc=120°C	$I_{(AV)}$	80.0 40.0	A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	400.0	A
Typical thermal resistance	$R_{\theta JC}$	1.5	°C/W
Operating junction temperature range	T_J	-55 to +175	°C
Storage temperature range	T_{STG}	-55 to +150	°C


Electrical Characteristics (Ta=25°C unless otherwise specified)

PARAMETER	SYMBOLS	TYPE	MAX	UNITS
Maximum instantaneous forward voltage per diode at 40.0A	V_F	0.95	1.0	V
Maximum DC reverse current at rated DC blocking voltage	I_R	0.5 2	50 20	u A mA

Ratings And Characteristic Curves

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT

FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG

FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS

FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS


Suggested Soldering Temperature Profile



Note

- Recommended reflow methods: IR, vapor phase oven, hot air oven, wave solder.
- The device can be exposed to a maximum temperature of 265°C for 10 seconds.
- Devices can be cleaned using standard industry methods and solvents.
- If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.

Package Information

Tube Package

Package	Tube (mm)	Q'TY/Tube (Kpcs)	Box Size (mm)	QTY/Box (Kpcs)	Carton Size (mm)	Q'TY/Carton (Kpcs)
TO-247	510*45.5*7.8	0.03	545*150*45	0.45	570*260*150	2.25